

CANOPIED DIESEL GENERATOR 5000W



FEATURES

- Top cover can be lifted up for easy access to fuel tank and maintenance work.
- Single cylinder 4 stroke vertical air-cooled diesel engine.
- Low oil sensor for engine protection (1.6 litre engine oil capacity).
- Digital 3 in 1 display measures Voltage, Frequency and Run Time.
- Automatic Voltage Regulator (AVR) to keep output (THD) to within 5%.
- Electric start using maintenance free sealed 12V DC 30Ah battery.
- Improved fuel supply system to avoid getting air in to the fuel lines during operation and maintenance.
- Rotating castors to allow multi-directional movement.
- Extra safety features such as separate circuit breaker for each socket and an emergency stop button.

SPECIFICATIONS

MAX. OUTPUT	5000W
CONTINUOUS OUTPUT	4500W
DISPLACEMENT	418cc
HORSE POWER	7.6HP
RUN TIME AT 50% LOAD	15h
OUTLETS	1 x 32A/240V 1 x 32A/110V 1 x 16A/110V
FUEL TANK CAPACITY	15L
FREQUENCY	50Hz

CANOPIED DIESEL GENERATOR 5000W



SPECIFICATIONS

LENGTH	910mm
WIDTH	532mm
HEIGHT	770mm
WEIGHT	165kg
FUEL TYPE	DIESEL
NOISE LEVEL	72dB(A) @ 7m
STARTING METHOD	ELECTRIC
AVR (AUTOMATIC VOLTAGE REGULATOR)	YES